

**KattenMuchinRosenman LLP**

75 Madison Ave.  
New York, NY 10022  
212.940.8800 tel  
(212) 940-8776 fax

**Facsimile**

To	Company	Fax Number	Phone Number
1. Examiner Thomas R. Hannon	USPTO – GAU 3656 Re: 10/566,956 Confirmation No. 9411	1-571-273-7104	

Date	Client/Matter Number
April 25, 2011	KAM 22.375 (100799-00124)
From	Attorney Email Address
Hassan Abbas Shakir	Hassan.shakir@kattenlaw.com
Phone	Fax
212.940.6489	212.940.8986

Total number of pages, including cover letter: 7  
If you do not receive all of the pages, please call: 212.940.8800

**\*\* EXPEDITED PROCEDURE \*\***

Enclosed:

**1 page – COVER LETTER**

**5 pages – SUMMARY OF ARGUMENTS TO BE PRESENTED  
DURING TELEPHONIC INTERVIEW**

Comments –

**For Messenger Department Use Only**

Your fax has been sent. Attached is your original.

Date \_\_\_\_\_ Time \_\_\_\_\_

Signature \_\_\_\_\_

**Important**

This facsimile transmission contains information intended for the exclusive use of the individual or entity to whom it is addressed and may contain information that is proprietary, privileged, confidential and/or exempt from disclosure under applicable law.

If you are not the intended recipient (or an employee or agent responsible for delivering this facsimile transmission to the intended recipient), you are hereby notified that any copying, disclosure or distribution of this information may be subject to legal restriction or sanction. Please notify the sender by telephone to arrange for the return or destruction of the information and all copies.

NEW YORK CHARLOTTE CHICAGO IRVING LOS ANGELES PALO ALTO WASHINGTON, DC WWW.KATTENLAW.COM

A law partnership including professional corporations

84336535\_1

# Katten

KattenMuchInRosenman LLP

575 Madison Avenue  
New York, NY 10022-3585  
212.940.8800 tel  
212.940.8778 fax

HASSAN ABBAS SHAKIR  
hassan.shakir@kattenlaw.com  
212.940.6469 direct  
212.940.6966 fax

April 25, 2011

**VIA FAX ONLY**

571.273.7104

Examiner Thomas R. Hannon  
U.S. Patent & Trademark Office  
Alexandria, VA 22313-1450

Re: U.S. Patent Application No.: 10/566,956  
Our Ref. No.: KAM 22.375 (100799-00124)

Dear Examiner Hannon:


Thank you for agreeing to schedule an interview. Enclosed please find a copy of a Draft Remarks serving as guidance for the interview scheduled for Thursday April 28 at 2:00 pm via telephone.

Absent instructions to the contrary, I will contact you at 571.272.7104.

I can be reached at 212.940.6489.

If you have any questions, please feel free to contact me.

Very truly yours,



Hassan Abbas Shakir,  
Reg. No. 53922

HS:fd  
Enclosures

Attorney Docket No.: KAM 22.375 (100799-00124)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Inventor(s): Akira TAKAHASHI  
Confirmation No.: 9411  
Serial No.: 10/566,956  
Filed: March 21, 2008  
Title: **SHELL-TYPE NEEDLE ROLLER BEARING**  
Examiner: Thomas R. HANNON  
Group Art Unit: 3656

April 25, 2011

Commissioner for Patents  
P. O. Box 1450  
Alexandria, VA 22313-1450

REMARKS

The following remarks serve as a basis for discussion in an interview. The claims are repeated solely as a convenience. No claim amendments are proposed.

- Page 1 of 5 -

U.S. Serial No. 10/566,956  
64519961\_100799-00124 KAM 22.375 (100799-00124) Remarks for Interview

**In the Claims:**

1. (previously presented) A shell-type needle roller bearing comprising:

a shell with both axial end portions of a cylinder portion bent radially inwards to form a pair of inward flange portions; and

a plurality of needles which are provided so as to roll freely on a radial inside portion of the cylinder portion between inside surfaces of both inward flange portions, without being retained by a cage, in a state where they are directly adjacent and facing or in contact with the rolling surfaces of circumferentially adjacent needles,

wherein the inside surfaces of both inward flange portions make up inclined surfaces which are inclined in a direction where a distance between the surfaces becomes narrower towards the radial outward direction, of both axial end surfaces of the needles, a portion nearer the center than a beveled portion on an outer peripheral portion, is shaped such that it does not project axially outwards more than an inner peripheral edge of the beveled portion, and in a state where the needles are displaced in the axial direction, contact portions between both axial end surfaces of the needles and the inside surfaces of the inward flange portions are positioned at portions close to the radial outside of the inward flange portions; and

wherein the angle of the inside surface of one of the both inward flange portions which has a flexural concave portion formed at a base end section thereof and depressed from an inner peripheral surface of the cylinder portion, with respect to a virtual plane which exists in a direction orthogonal to a central axis of the shell, is larger than the angle of the inside surface of the other inward flange portion on the opposite side which has no flexural concave portion with respect to the virtual plane.

2. (Original) A shell-type needle roller bearing according to claim 1, wherein an angle of the inside surfaces of both inward flange portions with respect to a virtual plane which exists in a direction orthogonal to a central axis of the shell, is 3 to 20 degrees, and at both axial end surfaces of the needles, a portion nearer the center than the beveled portion is a flat surface.

3. (previously presented) A shell-type needle roller bearing according to claim 1, wherein in relation to the radial direction of the shell, a distance between an inner peripheral edge of both inward flange portions and an inner peripheral surface of the cylinder portion, is made smaller than a diameter of the cross section of the needles, and larger than 1/3 of the diameter.

4. (previously presented) A shell-type needle roller bearing according to claim 1, wherein the needles are affixed to an inner peripheral surface of the shell using grease.

- Page 3 of 5 -

U.S. Serial No. 10/566,956

84319961\_100799-00124 KAM 22.375 (100799-00124) Remarks for Interview

**REMARKS**

Claims 1-4 are pending.

Claims 1-3 stand rejected under 35 U.S.C. §103(a) as being unpatentable over U.S. Patent No. 4,976,551 to Scharting in view of U.S. Patent No. 4,318,574 to Nakamura. Claim 4 stands rejected under 35 U.S.C. §103(a) as being unpatentable over Scharting, Nakamura and in view of U.S. Patent No. 3,501,210 to Deutsch.

Nakamura is cited at 4:53-58 for teaching a structure where one flange has a larger angle than the other. OA at 4. Applicant respectfully disagrees.

Nakamura discloses a structure where one guide surface 7 includes two faces: a first tapered annular face 7a and a second tapered annular surface 7b, as evidence by Fig. 2. These have different inclination angles  $\theta_1$ ,  $\theta_2$  from each other. This differs from the above technical idea of the presently claimed invention

*wherein the angle of the inside surface of one of the both inward flange portions which has a flexural concave portion formed at a base end section thereof and depressed from an inner peripheral surface of the cylinder portion, with respect to a virtual plane which exists in a direction orthogonal to a central axis of the shell, is larger than the angle of the inside surface of the other inward flange portion on the opposite side which has no flexural concave portion with respect to the virtual plane.*

In the presently claimed invention, one angle of the inside surface of one of the both inward flange portions which has a flexural concave portion is larger than the angle of the inside surface of the other inward flange portion on the opposite side which has no flexural concave portion with respect to the virtual plane. Nakamura teaches angles measured relative to the same side.

Nakamura is also cited for teaching at 4:53-58 that the angles of the taper surface can be freely selected from a range of angles depending upon the loading et al. OA at 4. Applicant respectfully disagrees.

- Page 4 of 5 -

U.S. Serial No. 10/566,956

8451961\_100799-00124 KAM 22.375 (100799-00124) Remarks for Interview

However, Nakamura does not disclose differentiating the angle of one tapered surface from that of the other. In Fig. 1 of Nakamura, the same numeral is given to the two tapered surfaces 7 which is formed on the opposite sides in the axial direction of the bearing 4 and these surfaces are depicted as having the same angle.

Therefore, one skilled person in the art would not achieve the structure of the present invention only referring to Nakamura and only the structure where the two tapered surfaces having the same angle can be adopted even when each of the tapered surfaces have two faces which have different angles from each other, unless the specific suggestion is provided. Nakamura fails to describe a reason why differentiating the angle of one tapered surface from that of the other.

With respect to claim 2, the rejection avers states that the tapered angles can be selected from a range of 3 to 20 degrees referring to Nakamura. OA at 5.

However, Nakamura discloses that the angle  $\theta_1$  of one face on the outer side of one guide surface 7 is 5° to 60° (5 minutes to 60 minutes) and the angle  $\theta_2$  of another face on the inner side of the one guide surface 7 is 10° to 120° (10 minutes to 120 minutes). 4:56-58. On the other hand in claim 2, the angle of 3 to 20 degrees corresponds to that of 180 to 1200 minutes, which do not overlap the values disclosed in Nakamura. Therefore, the present invention described in Claim 2 is not suggested by Nakamura.